



COMMERCIAL HEAT PUMP SPECIFICATIONS



| MODEL TYPE | SW-13.5 HPC | SW-24 HPC | SW-30 HPC | SW-38 HPC | SW-45 HPC | SW-55 HPC | SW-63 HPC | SW-90 HPC |
|--------------------------------------|---------------|-------------|--------------|---------------|---------------|---------------|---------------|----------------|
| Heating capacity KW | 13.5 | 24 | 30 | 38 | 45 | 55 | 63 | 90 |
| Input Power KW | 3.6 | 7.25 | 7.2 | 9.2 | 10.8 | 13.5 | 16 | 23.4 |
| COP | 3.6 | 3.3 | 4.17 | 4.13 | 4.17 | 4.07 | 3.94 | 3.8 |
| Power supply V/Ph/Hz | 230/1/50 | 380/3/50 | 380/3/50 | 380/3/50 | 380/3/50 | 380/3/50 | 380/3/50 | 380/3/50 |
| Running Current A | 16.7 | 9.4 | 12.0 | 15.8 | 18.6 | 23.4 | 27.5 | 23.0 |
| Compressor | Sanyo | Sanyo x 2 | Sanyo x 2 | Sanyo x 2 | Sanyo x 2 | Sanyo | Sanyo x 2 | Sanyo x 4 |
| Min/Max Operation Air temp °C | -15 +43 | -15 +43 | -15 +43 | -15 +43 | -15 +43 | -15 +43 | -15 +43 | -15 +43 |
| Max Setting Water temp °C | 60 | 60 | 60 | 60 | 60 | 60 | 60 | 60 |
| Water Connections mm | 28 | 28 | 42 | 42 | 42 | 54 | 54 | 54 |
| Fan Direction | Vertical | Vertical | Vertical | Vertical | Vertical | Vertical | Vertical | Vertical |
| Fan Speed RPM | 850 | 850 | 850 | 850 | 850 | 850 | 850 | 850 |
| Noise Level d B(A) | 58 | 60 | 58 | 60 | 60 | 58 | 60 | 60 |
| Unit Weight kg | 116 | 135 | 236 | 249 | 268 | 420 | 420 | 750 |
| Refrigerant | R 410-A | R 410-A | R 410-A | R 410-A | R 410-A | R 410-A | R 410-A | R 410-A |
| Unit dimension LxWxH(mm) | 1150x470x1250 | 860x780x980 | 1450x702x950 | 1450x702x1060 | 1450x702x1260 | 2150x765x1290 | 2150x765x1290 | 2270X1200X2100 |